

●:STANDARD ○:OPTIONAL - :N/A

NOMINAL DIAMETER		WALL THICKNESS		WEIGHT	ENDS					SURFACE TREATMENT						MARK			
INCH	MM	SCH	MM	KG/M	PLAIN END	BEVEL END	SCREWED AND SOCKETED	SWAGED	GROOVED	BARE	PAINTED	OILED	PRE-GALVANIZED	ELECTRO-GALVANIZED	HOT DIPPED GALVANIZED	EMB-OSSING	PRINT		
1/2"	0.84"	21.3	STD-40	2.77	1.27	●	○	○	-	-	●	○	○	-	○	○	○	●	
			80	3.73	1.62	●	○	○	-	-	●	○	○	-	○	○	○	○	●
3/4"	1.050"	26.7	STD-40	2.87	1.69	●	○	○	-	-	●	○	○	-	○	○	○	●	
			80	3.91	2.20	●	○	○	-	-	●	○	○	-	○	○	○	○	●
1"	1.315"	33.4	STD-40	3.38	2.50	●	○	○	-	-	●	○	○	-	○	○	○	●	
			80	4.55	3.24	●	○	○	-	-	●	○	○	-	○	○	○	○	●
1-1/4"	1.66"	42.2	STD-40	3.56	3.39	●	○	○	-	-	●	○	○	-	○	○	○	●	
			80	4.85	4.47	●	○	○	-	-	●	○	○	-	○	○	○	○	●
1-1/2"	1.90"	48.3	STD-40	3.68	4.05	●	○	○	-	-	●	○	○	-	○	○	○	●	
			80	5.08	5.41	●	○	○	-	-	●	○	○	-	○	○	○	○	●
2"	2.375"	60.3	STD-40	3.91	5.44	●	○	○	-	-	●	○	○	-	○	○	○	●	
			80	5.54	7.48	●	○	○	-	-	●	○	○	-	○	○	○	○	●
2-1/2"	2.875"	73.0	STD-40	5.16	8.63	●	○	○	-	-	●	○	○	-	○	○	○	●	
			80	7.01	11.41	●	○	○	-	-	●	○	○	-	○	○	○	○	●
3"	3.50"	88.9	STD-40	5.49	11.29	●	○	○	-	-	●	○	○	-	○	○	○	●	
			80	7.62	15.27	●	○	○	-	-	●	○	○	-	○	○	○	○	●
3-1/2"	4.00"	101.6	STD-40	5.74	13.57	●	○	○	-	-	●	○	○	-	○	○	○	●	
			80	8.08	18.63	●	○	○	-	-	●	○	○	-	○	○	○	○	●
4"	4.50"	114.3	STD-40	6.02	16.07	●	○	○	-	-	●	○	○	-	○	○	○	●	
			80	8.56	22.32	●	○	○	-	○	●	○	○	-	○	○	○	○	●
5"	5.563"	141.3	STD-40	6.55	21.77	●	○	○	-	-	●	○	○	-	○	○	○	●	
			80	9.52	30.94	●	○	○	-	○	●	○	○	-	○	○	○	○	●
6"	6.625"	168.3	STD-40	7.11	28.26	●	○	○	-	-	●	○	○	-	○	○	○	●	
			80	10.97	42.56	●	○	○	-	○	●	○	○	-	○	○	○	○	●
8"	8.625"	219.1	STD-40	8.18	42.55	●	○	○	-	-	●	○	○	-	○	○	○	●	
			80	12.07	64.64	●	○	○	-	○	●	○	○	-	○	○	○	○	●
10"	10.75"	273.0	STD-40	9.27	60.29	●	○	○	-	-	●	○	○	-	○	○	○	●	
			XS-60	12.70	81.52	●	○	○	-	○	●	○	○	-	○	○	○	○	●
			80	15.09	95.97	●	○	○	-	○	●	○	○	-	○	○	○	○	●
12"	12.75"	323.8	STD	9.52	73.78	●	○	○	-	-	●	○	○	-	○	○	○	●	
			40	10.31	79.70	●	○	○	-	○	●	○	○	-	○	○	○	○	●
			XS	12.70	97.43	●	○	○	-	○	●	○	○	-	○	○	○	○	●
			60	14.27	108.92	●	○	○	-	○	●	○	○	-	○	○	○	○	●
14"	14.00"	355.6	STD	9.52	81.25	●	○	○	-	-	●	○	○	-	○	○	○	●	
			40	11.13	94.55	●	○	○	-	○	●	○	○	-	○	○	○	○	●
			XS	12.70	107.39	●	○	○	-	○	●	○	○	-	○	○	○	○	●
			60	15.09	126.71	●	○	○	-	○	●	○	○	-	○	○	○	○	●
16"	16.00"	406.4	STD	9.52	93.17	●	○	○	-	-	●	○	○	-	○	○	○	●	
			XS-40	12.70	123.30	●	○	○	-	○	●	○	○	-	○	○	○	○	●
			60	16.66	160.12	●	○	○	-	○	●	○	○	-	○	○	○	○	●
18"	18.00"	457.0	STD	9.52	105.10	●	○	○	-	-	●	○	○	-	○	○	○	●	
			XS	12.70	139.20	●	○	○	-	○	●	○	○	-	○	○	○	○	●
			40	14.27	155.87	●	○	○	-	○	●	○	○	-	○	○	○	○	●
20"	20.00"	508.0	STD-20	9.52	117.02	●	○	○	-	-	●	○	○	-	○	○	○	●	
			XS-30	12.70	155.12	●	○	○	-	○	●	○	○	-	○	○	○	○	●
			40	15.09	183.42	●	○	○	-	○	●	○	○	-	○	○	○	○	●
24"	2400"	610.0	STD-20	9.52	140.88	●	○	○	-	-	●	○	○	-	○	○	○	●	
			XS	12.70	186.94	●	○	○	-	○	●	○	○	-	○	○	○	○	●
			40	17.48	255.24	●	○	○	-	○	●	○	○	-	○	○	○	○	●