

●:STANDARD ○:OPTIONAL - :N/A

RIGID METAL CONDUIT ANCI C80.1

| NOMINAL DIAMETER | OUTSIDE DIAMETER | INSIDE DIAMETER | WALL THICKNESS | WEIGHT |
|------------------|------------------|-----------------|----------------|--------|
| INCH | MM | MM | MM | KG/3M |
| 1/2 | 21.30 | 16.00 | 2.64 | 3.63 |
| 3/4 | 26.70 | 21.30 | 2.72 | 4.83 |
| 1 | 33.40 | 27.00 | 3.20 | 7.14 |
| 1 1/4 | 42.20 | 35.40 | 3.38 | 9.72 |
| 1 1/2 | 48.30 | 41.30 | 3.51 | 11.64 |
| 2 | 60.30 | 52.90 | 3.71 | 15.54 |
| 2 1/2 | 73.00 | 63.20 | 4.90 | 24.69 |
| 3 | 88.90 | 78.50 | 5.21 | 32.25 |
| 4 | 114.30 | 102.90 | 5.72 | 45.96 |
| 6 | 168.30 | 154.80 | 6.76 | 80.79 |

INTERMEDIATE METAL CONDUIT ANCI C80.6

| NOMINAL DIAMETER | OUTSIDE DIAMETER | INSIDE DIAMETER | WALL THICKNESS | WEIGHT |
|------------------|------------------|-----------------|----------------|--------|
| INCH | MM | MM | MM | KG/3M |
| 1/2 | 20.83 | 16.87 | 1.98 | 2.76 |
| 3/4 | 26.26 | 22.08 | 2.09 | 3.72 |
| 1 | 32.89 | 28.19 | 2.35 | 5.31 |
| 1 1/4 | 41.78 | 36.94 | 2.42 | 7.05 |
| 1 1/2 | 48.01 | 42.93 | 2.54 | 8.55 |
| 2 | 60.12 | 54.78 | 2.67 | 11.34 |

